

Product datasheet

Specifications



APC NetShelter Soundproof, 32U, Server Rack Enclosure, 230V, Maple

AR4032IA

Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Product or component type	Rack enclosure
Main Input Voltage	230 V
Input Connection Type	IEC 60320 C20
output connection type	8 IEC 60320 C13
Number of rack unit	32U
Cable length	2.49 m
Number of cables	1
Provided equipment	Casters

Physical

Height	1675 mm
Width	750 mm
Depth	1130.4 mm
Net weight	216 kg
Colour	Maple
Mounting preference	No preference
Mounting mode	Not rack-mountable
Mounting position	Horizontal
Maximum mounting depth	0.83 m
minimum mounting depth	0.69 m
Rack width	19"
Permanent permissible load	1500 kg static

Input

Network frequency	50/60 Hz
-------------------	----------

Output

PDU type	Basic
----------	-------

Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	EIA-310D
-----------	----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	178.7 cm
Package 1 Width	82 cm
Package 1 Length	120 cm
Package 1 Weight	260 kg

Contractual warranty

Warranty	2 Years
----------	---------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	789
Use Better	
Materials and Substances	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Use Again	
Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No