

Product datasheet

Specifications



Rack PDU, Basic, 0U/1U, 220-240V, 63A, (3) C19



AP6038A

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.7 m
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	230 V 240 V
Height	4.4 cm
Width	38.8 cm
Depth	12.6 cm
Net weight	5.4 kg
Mounting location	Front
Mounting preference	No preference
Input Plug Type	IEC 60309 63 A 2P + PE
Mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
Permissible voltage	200...240 V
Max line current	48 A
Input current limits	48 A
Load capacity	14500 VA
Network frequency	50/60 Hz
Outlet type and quantity	3 IEC 60320 C19

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE EAC IRAM VDE
------------------------	--------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.5 cm
Package 1 Width	19.5 cm
Package 1 Length	50 cm
Package 1 Weight	8.3 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint		
Environmental Disclosure		Product Environmental Profile
Use Better		
Materials and Substances		
EU RoHS Directive		Compliant
REACH Regulation		REACH Declaration
Energy efficiency		
Optimized Energy Efficiency		Energy efficient product
Use Again		
Repack and remanufacture		
Circularity Profile		End of Life Information
Take-back		Yes