



APC Back-UPS Pro for Gaming, Back-UPS Pro, 2200VA/1320W, Tower, 230V, 6x Australian outlets, RGB Lights, Pure Sine Wave, Midnight (Black)

BGM2200B-AZ

#### **Overview**

Lead time	Usually in Stock
Main	
Main Input Voltage	230 V AC 1 phase
Other Input Voltage	230 V
Main Output Voltage	230 V 1 phase
Rated power in W	1320 W
Rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Australian
output connection type	6 Australian surge 6 Australian
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Overcurrent protection	15 A
Battery charger power	12 W rated
Battery life	35 year(s)

#### **General**

Provided equipment	safety guide USB cable power cable
product web sub-family	Gaming performance
Number preinstalled power module	0
Number of power module free slots	0
Redundant	No

# **Physical**

•	
Colour	Black
Height	292.1 mm
Width	104.1 mm
Depth	408.9 mm
Net weight	12.56 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

# Input

Network frequency	50/60 Hz +/- 3 Hz
Plug standard	Australian
Input voltage limits	168302 V
Maximum input current	12 A
Switching current capacity	15 A
Input harmonic distortion	Less than 3 % for full load
Input protection type	Circuit breaker

## Output

Maximum configurable power in W	1320 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Full load runtime	00:30:00
Half load runtime	00:04:19
Maximum configurable power in VA	2200 VA
Transfer time	8 ms typical : 10 ms maximum

## Conformance

Product certifications	CE
	CB

Equipment protection policy Lifetime: \$150000

#### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 %
Storage altitude	0.00000000003048.000000000 m
Acoustic level	45 dBA
IP degree of protection	IP20

## **Communications & Management**

Free slots	0
control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

# **Surge Protection and Filtering**

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.38 kg
SCC14	20731304634809

## **Contractual warranty**

Warranty 2 years repair or replace, 3 years repair or replace for European Union countries



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

0	<b>Environmental footprint</b>	
V	Environmental tootprint	

Environmental Disclosure Product Environmental Profile

#### **Use Better**

# Materials and Substances EU RoHS Directive Compliant with Exemptions

**REACh Declaration** 

#### **Use Again**

REACh Regulation

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No

## BGM2200B-AZ

Image of product / Alternate images

**Alternative** 

