Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





APC Symmetra RM 8-12kVA Power Module (4kVA)

SYPM4KU

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.	
Lead time	Usually in Stock	

Main	
Main Input Voltage	200 V
	208 V
	230 V
Product or component type	Power module
Other Input Voltage	220 V
Main Output Voltage	200 V
	208 V
	230 V
Other Output Voltage	220 V
Rated power in W	2800 W
Rated power in VA	4000 VA
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	0U
Provided equipment	Installation guide
Range of product	Symmetra Power Module

Batteries & Runtime

Run Time	View Runtime Graph ☐
Number of battery filled slots	0
Number of battery free slots	0

Physical

Height	15 cm
Width	25 cm
Depth	59 cm
Net weight	15 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0

USB compatible No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	155276 V

Output

Maximum configurable power in W	2800 W
Harmonic distortion	Less than 3 %
Output frequency	50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	Up to 5:1
Wave type	Sine wave

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.9 cm
Package 1 Width	79 cm
Package 1 Length	33 cm
Package 1 Weight	18.18 kg

Contractual warranty

Warranty 2 years



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Ø	Environmental	footprint
		100tpi iiit

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant

REACh Regulation REACh Declaration

Use Again

○ Repack and remanufacture

Circularity Profile <u>End of Life Information</u>

Take-back No