

Product datasheet

Specifications



Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC 309-32



AP7586

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	8.5 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	8.9 cm
Width	43.7 cm
Output Voltage	230 V
Depth	8.9 cm
Net weight	4.1 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire
Outlet type and quantity	4 IEC 60309

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE VDE
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	52.1 cm
Package 1 Length	52.1 cm
Package 1 Weight	4.99 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	102
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes