Specifications



APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, Network Card, Extended runtime, W/ rail kit

SRT1000RMXLI-NC

#### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.	
Lead time	Usually in Stock	
Main		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	1000 W	
Rated power in VA	1000 VA	
Input Connection Type	BS1363A British IEC 60320 C14 Schuko CEE 7 / EU1-16P	
output connection type	6 IEC 60320 C13	
Number of rack unit	2U	
Cable length	1.8 m	
Number of cables	1	
Provided equipment	CD with software Communication cable Country-specific detachable power cord Documentation CD Installation guide Network management card Rack mounting hardware Rack mounting brackets Rack mounting support rails Temperature probe USB cable Warranty card	
Range of product	Smart-I IPS On-I ine	

Range of product

Smart-UPS On-Line

#### **Batteries & Runtime**

Run Time	View Runtime Graph	
Battery type	Lead-acid battery	
Battery voltage	48 V	
Extended runtime	1	
Number of battery filled slots	1	

Number of battery free slots	0	
Battery recharge time	3 h	
Number of battery replacement quantity	1	
Battery life	35 year(s)	
Replacement battery	APCRBC155	
Battery charger power	97 W rated	

## General

Number of power module filled slots	0	
Number of power module free slots	0	
product web sub-family	High density	
Redundant	No	
UPS type	Double conversion online	

# Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	50.5 cm
Net weight	21 kg
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

# Input

Input voltage limits	176275 V full load 100275 V
Network frequency	4070 Hz auto-sensing

# Output

Bypass type	Built-in bypass
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	1000 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	CE EAC UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006
	EN/IEC 62040-2:2018

#### Environmental

Acoustic level	50 dBA	
Heat dissipation	317 Btu/h	
Operating altitude	010000 ft	
Ambient air temperature for operation	040 °C	
Ambient air temperature for storage	-2050 °C	
Storage altitude	0.00000000015240.000000000 m	
IP degree of protection	IP20	
Relative humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

### **Communications & Management**

Emergency power off	Yes	
Free slots	0	
Preinstalled device	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

### **Surge Protection and Filtering**

Surge energy rate

432 J

#### **Packing Units**

V	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	69.0 cm
Package 1 Length	59.5 cm
Package 1 Weight	32.58 kg

#### **Contractual warranty**

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

Life Is On Schneider

# 🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability  $\geq$ 

# Image: Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 1843

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
ℰ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
Use Again	
$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes