



APC Back-UPS Pro, Back-UPS Pro, 1600VA/960W, Tower, 230V, 8x IEC C13 outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

BR1600SI

Overview

Lead time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	960 W
Rated power in VA	1600 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C13
output connection type	6 IEC 60320 C13 2 IEC 60320 C13 surge
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.4 Ah
Battery charger power	16 W rated
Battery life	35 year(s)
Replacement battery	APCRBC163 ☐
Extended runtime	0

General

Provided equipment user manual USB cable

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	26 cm
Width	10 cm
Depth	36.8 cm
Net weight	12.1 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

•	
Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Input voltage limits	176294 V
Maximum input current	10 A
Switching current capacity	10 A

Output

Maximum configurable power in W	960 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Maximum configurable power in VA	1600 VA

Conformance

Product certifications	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 % non-condensing

Storage altitude	0.000000000015240.0000000000 m
Acoustic level	45 dBA
Heat dissipation	19.5 Btu/h

Communications & Management

control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone

Surge Protection and Filtering

Surge energy rate	509 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.9 cm
Package 1 Width	48.2 cm
Package 1 Length	22.3 cm
Package 1 Weight	13.75 kg
SCC14	10731304346927

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries and
	UK



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∅ Environmental footprint

Environmental Disclosure

Optimized Energy Efficiency

Product Environmental Profile

Energy efficient product

Use Better

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
[⋯] Energy efficiency	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes