# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# In-Line Current Meter, 16A, 230V, IEC309-16A, 2P+G

AP7152B

## Overview

Lead time Usually in Stock

# Main

Colour	Black	
Product or component type	PDU	
Cord length	0.9 m	
Number of cables	1	
Provided equipment	Documentation CD Rack mounting brackets RS-232 configuration cable	

# **Complementary**

Complementary		
Input Voltage	200 V 208 V 230 V	
Height	4.4 cm	
Width	17.8 cm	
Output Voltage	230 V	
Depth	14 cm	
Net weight	1.84 kg	
Mounting location	Тор	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Permissible voltage	220250 V	
Max line current	16 A	
Input current limits	16 A	
Load capacity	3680 VA	
Number of power socket outlets	1	
Network frequency	50/60 Hz	
Outlet type and quantity	1 IEC 60309 16 A 2P + E	

# **Environment**

Product certifications	AS/NZS 3548 (C-Tick) class A C-Tick CE GOST VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 IEC 61000-3-2 IEC 61000-3-3
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	18.5 cm
Package 1 Length	33 cm
Package 1 Weight	2.48 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	47
Environmental Disclosure	Product Environmental Profile

### **Use Better**

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
<sup>™</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Removable battery	Yes	
Take-back	Yes	