



# RACK PDU, BASIC, 0U/1U, 120-240V/15A, 220-240V/10A, (8) C13

AP6015A

## Overview

Lead time Usually in Stock

## Main

Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Provided equipment	Installation guide Safety guide	

# Complementary

	,	
Input Voltage	100 V	
	120 V	
	200 V	
	208 V	
	230 V	
	240 V	
Height	24 cm	
Width	4.4 cm	
Output Voltage	100 V	
	120 V	
	200 V	
	208 V	
	230 V	
	240 V	
Depth	9.3 cm	
Net weight	0.91 kg	
Mounting location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60320 C14	
Mounting mode	Not rack-mountable	
Rack units	1U	
Mounting position	Horizontal	
[In] rated current	12 A	
Permissible voltage	100240 V	
Max line current	15 A	
Input current limits	15 A	

Load capacity	2300 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	8 IEC 60320 C13	

## **Environment**

Product certifications	cUL listed	
	CE	
	EAC	
	IRAM	
	UL listed	
	VDE	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	13 cm
Package 1 Length	21 cm
Package 1 Weight	1.37 kg
SCC14	10731304327797

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	24
Environmental Disclosure	Product Environmental Profile

## **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
<sup>™</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Product contains halogen above thresholds
Take-back	Yes