

Product datasheet

Specifications



APC Back-UPS, Back-UPS, 1600VA, 230V, AVR, 4 Australian outlets

BX1600MI-AZ

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	900 W
Rated power in VA	1600 VA
Product or component type	Uninterruptible power supply (UPS)
Output connection type	4 Australian
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery life	3...5 year(s)
Replacement battery	APCRBC176
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0

General

Provided equipment	user manual
Number of power module free slots	0
Number of power module filled slots	0

Redundant	No
-----------	----

Physical

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	10.3 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V
Input Power Factor at Full Load	0.56

Output

Maximum configurable power in W	900 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 900 W
Half load runtime	00:06:30 450 W
Maximum configurable power in VA	1600 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB RCM
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA

IP degree of protection IP20

Communications & Management

control panel LED Status display with on line : on battery

Surge Protection and Filtering

Surge energy rate 273 J

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 29.7 cm

Package 1 Width 49.5 cm

Package 1 Length 23.5 cm

Package 1 Weight 11.3 kg

SCC14 10731304410772

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No