



APC Back-UPS Connect, Back-UPS Connect, to protect internet routers, IP cameras and more

CP12036LI

Overview

Lead time Usually in Stock

Main

Main Input Voltage	12 V DC	
Product or component type	Uninterruptible power supply (UPS)	
Main Output Voltage	12 V DC	
Battery type	Li-lon (Lithium-lon)	
Range of product	Back-UPS Connect	

Complementary

Number of tare power 2 W

Batteries & Runtime

Battery recharge time 9

Physical

Colour	White
Width	99 mm
Depth	109 mm
Net weight	300 g
Mounting mode	Not rack-mountable
Height	25 mm

Output

Maximum configurable power in W	36 W
Output voltage	12 V

Conformance

Product certifications	CE	
Standards	CE	
	EN/IEC 61000-4-8	
	EN/IEC 61000-4-2	
	EN/IEC 62369 1	

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1050 °C
Storage altitude	05000 m
IP degree of protection	< IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.300 cm
Package 1 Width	11.500 cm
Package 1 Length	16.300 cm
Package 1 Weight	366.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.900 kg
SCC14	10731304632396

Contractual warranty

Warranty 24 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Removable battery	Yes
Take-back	No