

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 22kW, 400V, (6) C19 & (3) C13

AP7555A

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	1.8 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit

Complementary

Input Voltage	400 V 3 phases
Height	92.7 cm
Width	5.5 cm
Output Voltage	230 V
Depth	8.8 cm
Net weight	4.76 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Permissible voltage	200...250 V
Max line current	32 A
Load capacity	22000 VA
Network frequency	47...63 Hz
Outlet type and quantity	3 IEC 60320 C13 6 IEC 60320 C19

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE GOST VDE
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	106.7 cm
Package 1 Width	29.8 cm
Package 1 Length	8.3 cm
Package 1 Weight	6.247 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

🌱 Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	120
Environmental Disclosure	Product Environmental Profile

Use Better

♻️ Materials and Substances	
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

💡 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

🔄 Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes