Specifications



Rack PDU, Basic, 1U, 22kW, 400V, (6) C19

AP7526

Overview

Lead time

Usually	in	Stock
Usually		OLUCK

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.4 m
Number of cables	1
Provided equipment	Installation guide

Complementary

Input Voltage	400 V 3 phases
Height	4.4 cm
Width	43.7 cm
Output Voltage	230 V
Depth	25.4 cm
Net weight	4.84 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Permissible voltage	200250 V
Max line current	32 A
Input current limits	32 A
Load capacity	22000 VA
Network frequency	4763 Hz
Outlet type and quantity	6 IEC 60320 C19

Environment

Product certifications	CE GOST VDE
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	55.9 cm
Package 1 Length	50.2 cm
Package 1 Weight	6.965 kg

Contractual warranty

Warranty

2 years repair or replace

🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

124

Environmental Data explained >

How we assess product sustainability \geq

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)

Product Environmental Profile

Use Better

S Materials and Substances		
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	
Inergy efficiency		
Optimized Energy Efficiency	Energy efficient product	
Use Again		
\circlearrowright Repack and remanufacture		
Circularity Profile	End of Life Information	

Take-back

Yes