

Specifications





APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 8x C13+2x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit

SRT2200RMXLI-NC

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime. Usually in Stock	
Lead time		
Main		
Main Input Voltage	230 V	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V 240 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V 240 V	
Rated power in W	1980 W	
Rated power in VA	2200 VA	
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P	
output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19	
Number of rack unit	2U	
Cable length	2.4 m	
Number of cables	1	
Provided equipment	CD with software Country-specific detachable power cord Documentation CD Installation guide Network management card Rack mounting hardware Rack mounting brackets Rack mounting support rails USB cable Warranty card	

Range of product

Smart-UPS On-Line

Batteries & Runtime

Run Time	View Runtime Graph □
Efficiency	View Efficiency Graph 🖾
Battery type	Lead-acid battery
Battery voltage	72 V

Extended runtime	1
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC141
Battery charger power	122 W rated

General

Number of power module	1400	
Number of power module filled slots	0	
Number of power module free slots	0	
product web sub-family	High density	
Redundant	No	
UPS type	Double conversion online	

Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	58.4 cm
Net weight	25 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Input voltage limits	limits 100275 V adjustable (half load)	
Network frequency	4070 Hz auto-sensing	

Output

Bypass type	Built-in bypass
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Wave type	Sine wave

Output frequency

Conformance

Product certifications	CE EAC RCM VDE UK PSTI
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA	
Heat dissipation	535 Btu/h	
Operating altitude	010000 ft	
Ambient air temperature for operation	040 °C	
Ambient air temperature for storage	-2050 °C	
Storage altitude	0.00000000015240.000000000 m	
IP degree of protection	IP20	
Relative humidity	095 % non-condensing	
Storage Relative Humidity	095 % non-condensing	

Communications & Management

Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity

Surge Protection and Filtering

Surge energy rate

340 J

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.500 cm
Package 1 Width	60.000 cm
Package 1 Length	81.500 cm
Package 1 Weight	33.105 kg
Unit Type of Package 2	P12
Number of Units in Package 2	3
Package 2 Height	90.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm

Package 2 Weight

111.315 kg

Contractual warranty

Warranty

3 years repair or replace (excluding battery) and 2 years for battery

L Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

3657

Environmental Data explained >

How we assess product sustainability >

${\mathcal Q}$ Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)

Environmental Disclosure

Removable battery

Take-back

Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
ℰ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
Use Again	
igcup Repack and remanufacture	
Circularity Profile	End of Life Information

User replaceable

Yes