



APC NetShelter Metered Rack PDU, 2U, 1PH, 7.4kW 230V 32A, x12 C13 and x4 C19 outlets, IEC 309 cord

AP7822B

Overview

Lead time	Usually in Stock

Main

Product or component type	PDU	
PDU type	Metered	
Cord length	3.7 m	
Number of cables	1	
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual	

Complementary

Input Voltage	200 V 208 V 230 V	
Height	8.8 cm	
	0.0 CIII	
Width	44.4 cm	
Output Voltage	230 V	
Depth	11.2 cm	
Net weight	3.36 kg	
Mounting location	Front Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	2U	
Mounting position	Horizontal	
Input current limits	32 A	
Load capacity	7400 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	12 IEC 60320 C13 4 IEC 60320 C19	

Environment

Product certifications	C-Tick CE GOST IRAM MIC VDE VCCI
Standards	FCC part 15 class A ICES-003
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	5.42 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	8952
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes