Specifications



## APC NetShelter Rack PDU Advanced, Metered, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APDU10350ME

Overview		
Lead time	Usually in Stock	
Main		
Colour	Black	
Product or component type	PDU	
PDU type	Metered	
Cord length	1.8 m	
Complementary		
Input Voltage	415 V 3 phases 400 V 3 phases	
Height	178.0 cm	
Width	5.6 cm	
Output Voltage	240 V	
Depth	7.5 cm	
Net weight	8.4 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 30 A 3P + N + PE	
Mounting mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	24 A	
Permissible voltage	200240 V 346415 V	
Input current limits	30 A	
Load capacity	17300 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	24 C13/C15/C19/C21 24C13/C15	

### Environment

Product certifications	TAA compliance BAA compliance	
Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1	
IP degree of protection	IP44	
Ambient air temperature for operation	-560 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	0.00000000015240.000000000 m	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	198 cm
Package 1 Width	13.2 cm
Package 1 Length	26.2 cm
Package 1 Weight	11.4 kg

## **Contractual warranty**

Warranty

3 years repair or replace

## 🜔 Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

# Image: Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 13750 Environmental Disclosure Product Environmental Profile

#### **Use Better**

S Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

#### Use Again

$\circlearrowright$ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No