

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19

AP8659EU3

## **Overview**

Presentation

APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time

Usually in Stock

#### Main

Colour	Black	
Product or component type	PDU	
PDU type	Switched metered outlet	
Cord length	3.00 m	
Provided equipment	CAN port terminator Installation guide Locking input power cord Rack mounting brackets Safety guide Serial configuration cable	

# Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	182.9 cm	
Width	5.6 cm	
Output Voltage	230 V	
Depth	5.1 cm	
Net weight	6.77 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 2P + E	
Mounting mode	Not rack-mountable	

Rack units	0U	
Mounting position	Vertical	
Permissible voltage	100240 V	
Input current limits	16 A	
Load capacity	3700 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19	

# **Environment**

Product certifications	PSE UL listed VCCI class A VDE	
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003	
Ambient air temperature for operation	-560 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	0.000000000015240.0000000000 m	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203.8 cm
Package 1 Width	16.2 cm
Package 1 Length	11.7 cm
Package 1 Weight	9.031 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	7442
Environmental Disclosure	Product Environmental Profile

## **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
᠃ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

## **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes