



## APC Smart-UPS On-Line SRT Battery Pack for 8/10kVA Extended runtime model 192V

SRT192BP2

### Overview

Lead time Usually in Stock

### Main

Product or component type	Battery
Battery type	Lead-acid battery
Provided equipment	Documentation CD Installation guide Warranty card
Range of product	Smart-UPS Battery Systems

## **Batteries & Runtime**

Number of battery free slots	0	
Number of battery filled slots	0	
Device mounting	Stand alone battery stack	
Battery voltage	+/- 192 V	
Number of battery replacement quantity	2	
Replacement battery	APCRBC140 ☐	

## **Physical**

Colour	Black
Height	43.2 cm
Width	13 cm
Depth	68.27 cm
Net weight	91 kg
Mounting mode	Rack-mounted with kit

## **Environmental**

Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 % non-condensing	
Ambient air temperature for storage	-1545 °C	
Storage altitude	0.000000000015240.000000000 m	
Storage Relative Humidity	095 % non-condensing	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	42.000 cm
Package 1 Width	100.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	101.500 kg

## **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	465
Environmental Disclosure	Product Environmental Profile

### **Use Better**

<b>⊗</b> Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes