

Product datasheet

Specifications



APC KVM 2G, Server Module, PS/2 with Virtual Media

KVM-PS2VM

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Server
---------------------------	--------

Physical

Height	1.4 cm
Width	12.5 cm
Depth	12.5 cm
Net weight	0.14 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Conformance

Product certifications	C-Tick CE TAA compliance VCCI class A
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for operation	0...50 °C
Operating altitude	0...10000 ft
Relative humidity	5...95 %
Ambient air temperature for storage	-10...60 °C
Storage altitude	0.0000000000...3048.0000000000 m
Storage Relative Humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	12.9 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	12.5 cm
Package 1 Weight	0.18 kg
SCC14	10731304286667

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant

Use Again

 Repack and remanufacture	
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No