

Rack PDU, Switched, Zero U, 10A, 230V, (16) C13

AP7950B

Overview

Lead time Usually in Stock

Main

Colour	Black	
Product or component type	PDU	
PDU type	Switched	
Cord length	3.05 m	
Number of cables	1	
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit User manual	

Complementary

	~	
Input Voltage	200 V	
	208 V	
	230 V	
	200 V	
Height	124.5 cm	
Width	5.6 cm	
Output Voltage	230 V	
Double		
Depth	4.4 cm	
Net weight	4.32 kg	
 		
Mounting location	Rear	
Mounting preference	No preference	
Input Plug Type	IEC 60320 C14	
Mounting mode	Rack-mounted	
Rack units	ALL.	
Rack units	0U	
Mounting position	Vertical	
Permissible voltage	200240 V	
80 U		
Max line current	10 A	
Input current limits	10 A	
Load capacity	2300 VA	
Network frequency	4763 Hz	
	7700 112	

Outlet type and quantity 16 IEC 60320 C13

Environment

Product certifications	CE GOST IRAM VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	5.23 kg

Contractual warranty

Warranty 2 years repair or replace

12 Mar 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1735		
Environmental Disclosure	Product Environmental Profile		

Use Better

EU RoHS Directive	Compliant with Exemptions	
REACh Regulation	REACh Declaration	
Optimized Energy Efficiency	Energy efficient product	

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Removable battery	Yes	
Take-back	Yes	