

Product datasheet

Specifications



APC KVM 2G, Digital/IP, 1 Remote/1 Local User, 16 Ports with Virtual Media - FIPS 140-2

KVM1116R

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	24 V DC 100 V 120 V 208 V 230 V 240 V
Product or component type	Switch
Number of rack unit	1U

Physical

Colour	Black
Height	4.3 cm
Width	42.4 cm
Depth	18.8 cm
Net weight	2.59 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50/60 Hz
-------------------	----------

Conformance

Product certifications	C-Tick CE EAC TAA compliance UL-AR VCCI class A VDE
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for operation	0...50 °C
---------------------------------------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Relative humidity	0...80 %
Ambient air temperature for storage	-20...60 °C
Storage altitude	0.0000000000...15240.0000000000 m
Storage Relative Humidity	0...80 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.6 cm
Package 1 Width	33 cm
Package 1 Length	61.9 cm
Package 1 Weight	3.99 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No