# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Easy UPS 3S Battery Breaker Box

E3SOPT007

### Overview

Presentation	Wall mounted battery breaker box for use with third party battery solutions.
Lead time	Usually Ships within 6 Weeks

## Main

Product or component type	Box
Battery type	VRLA
Range of product	Easy UPS 3S
Range compatibility	Easy UPS 3S

# **Batteries & Runtime**

Number of battery filled slots	0
Number of battery free slots	0

# **Physical**

Height	65 cm
Width	50 cm
Depth	28 cm
Net weight	25 kg
Mounting mode	Not rack-mountable

### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03333 ft
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	122 cm

Package 1 Width	51 cm
Package 1 Length	85 cm
Package 1 Weight	46.5 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### **Use Better**

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration