Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Easy UPS 3S Cold Start Kit

E3SOPT004

Overview

Presentation	Cold start kit that enables the Easy UPS 3S UPS to start up on battery power. The kit includes a cold start board, button, and cables.
Lead time	Usually Ships within 6 Weeks

Main

Product or component type	Kit
Range of product	Easy UPS 3S
Range compatibility	Easy UPS 3S

Physical

Height	2.4 cm
Width	2.1 cm
Depth	6.3 cm
Net weight	0.1 kg
Mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	040 °C	
Relative humidity	095 % non-condensing	
Operating altitude	03333 ft	
Ambient air temperature for storage	-1540 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	0.000000000015240.0000000000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 cm
Package 1 Width	6.3 cm
Package 1 Length	2.1 cm
Package 1 Weight	0.1 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
Take-back	No	