

# Product datasheet

Specifications



## Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m, Red

AP8706S-WWX340

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C14
Cable length	1.8 m

### Physical

Colour	Red
Height	24 cm
Width	7.5 cm
Depth	5.5 cm
Net weight	1.35 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Max line current	10 A
Input current limits	10 A

### Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	1.8 m

### Conformance

Product certifications	CCC PSE VDE
------------------------	-------------------

### Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	5.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	1.35 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------





## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

<div><div></div><div>Environmental footprint</div></div>		
Environmental Disclosure		<a href="#">Product Environmental Profile</a>
Use Better		
<div><div></div><div>Materials and Substances</div></div>		
<a href="#">EU RoHS Directive</a>		Compliant
REACH Regulation		<a href="#">REACH Declaration</a>
<div><div></div><div>Energy efficiency</div></div>		
Optimized Energy Efficiency		Energy efficient product
Use Again		
<div><div></div><div>Repack and remanufacture</div></div>		
Circularity Profile		<a href="#">End of Life Information</a>
Take-back		Yes