



APC Smart-UPS On-Line, 5kVA, Rackmount 3U, 208V/230V, Hard wire 3-wire(2PH+G)+3wire(H+N+E)+3-wire(H+N+G) outlets, Network Card+SmartSlot, W/ rail kit

SRT5KRMXLW-HW

#### **Overview**

Rated power in VA

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock
Main	
Main Input Voltage	208 V 230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	208 V 230 V
Other Output Voltage	220 V 240 V
Rated power in W	4500 W

Output connector type

Hard wire 3-wire (H N + E) 1

Hard wire 3-wire (2P + F) 1

5000 VA

Hard wire 3-wire (2P + E) 1

Number of rack unit 3U

Provided equipment CD with software

Documentation CD
Installation guide
Rack mounting hardware
Rack mounting support rails
Removable support feet
Temperature probe
User manual
Warranty card

Range of product Smart-UPS On-Line

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery type	Lead-acid battery
Battery voltage	192 V
Extended runtime	1

Web/SNMP management card

Number of battery filled slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC140 ☐
Battery charger power	560 W rated

### General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	High density
Redundant	No
UPS type	Double conversion online

## **Physical**

Colour	Black
Height	13 cm
Width	43.2 cm
Depth	71.9 cm
Net weight	55.79 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

### Input

Input voltage limits	100275 V adjustable (half load)
Number of input connectors	1 hard wire 3-wire (2P + E) 1 hard wire 3-wire (1P + N + E)
Network frequency	4070 Hz auto-sensing

## Output

Bypass type	Internal bypass (automatic and manual)
Crest factor	3:1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	5000 VA
Maximum configurable power in W	4500 W
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

#### Conformance

Product certifications	CE EAC ENERGY STAR V2.0 (USA) FCC part 15 class A IRAM NOM RCM UL 1778 VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

### **Environmental**

Acoustic level	55 dBA
Heat dissipation	931 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
IP degree of protection	IP20
Relative humidity	095 % non-condensing
Storage Relative Humidity	095 % non-condensing

## **Communications & Management**

Emergency power off	Yes	
Free slots	1	
Preinstalled device	Network management card 3 with environmental monitoring	
Alarm	Audible and visible alarms : prioritized by severity	

# **Surge Protection and Filtering**

Curao energy rete	480 J
Surge energy rate	480 J

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	96 cm
Package 1 Length	61 cm
Package 1 Weight	68.04 kg

### **Contractual warranty**



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	8442
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
<sup>⋯</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes