



# Power Cord, Locking C19 to Rewireable, 3.0m

AP8759

#### Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

#### Main

Product or component type	Power cord
Main Output Voltage	240 V
Cable length	3.05 m
Number of cables	1

# **Physical**

Colour	Black
Height	23 cm
Width	23 cm
Depth	4.5 cm
Net weight	0.37 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

## Input

Number of input connectors	1 hard wire 3-wire
Max line current	16 A
Input current limits	16 A

## **Output**

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3.05 m

#### **Conformance**

Product certifications	VDE		
------------------------	-----	--	--

#### **Environmental**

Ambient air temperature for operation	070 °C
Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2070 °C
Storage Relative Humidity	2080 %
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	23 cm
Package 1 Length	4.5 cm
Package 1 Weight	0.37 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	26 cm
Package 2 Width	34 cm
Package 2 Length	57 cm
Package 2 Weight	10 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	25
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	10 kg
SCC14	10731304279829

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

<b>⊘</b> Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	116
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

<b>⊗</b> Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

#### Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes