

Rack PDU 2G, Metered, ZeroU, 32A, 230V, Clipsal 56 series AS/ NZ input plug, (36) C13 & (6) C19 outlets

AP8853X678

Overview	
Presentation	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using StruxureWare software suite.

Lead time

Special Order - Call for Quoted Lead Times

## Main

Product or component type	PDU
PDU type	Metered
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Serial configuration cable

# Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	179.1 cm	
Width	5.6 cm	
<del></del>		
Output Voltage	230 V	
Danish		
Depth	4.4 cm	
Net weight	6.93 kg	
	0.95 kg	
Mounting location	Side	
Mounting preference	No preference	
	·	
Mounting mode	Not rack-mountable	
Rack units	0U	
Mounting position	At a l	
Mounting position	Vertical	
Permissible voltage	220240 V	
	220270 ¥	
Max line current	32 A	
Input current limits	32 A	
-		

Network frequency	50/60 Hz	
Number of input connectors	1 clipsal 32A 56P332	
Outlet type and quantity	36 IEC 60320 C13 6 IEC 60320 C19	

## **Environment**

Product certifications	VDE
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000 15240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200 cm
Package 1 Width	10.7 cm
Package 1 Length	16.2 cm
Package 1 Weight	8.56 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

## ☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes