Product datasheet

Specifications

Round guard for 40mm Emergency stop, Harmony XB4, plastic, yellow, 76.2mm

ZB4BZ2105

Main

Range of product	Harmony XB5 Harmony XB4
Product or component type	Guard
Accessory / separate part category	Protection accessory
Accessory / separate part destination	Ø 40 mm emergency stop push-button
Colour	Yellow
Quantity per set	Set of 1

Complementary

Material	Plastic
Net weight	0.058 kg

Environment

Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…70 °C
IK degree of protection	IK05

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	8.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	58.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.552 kg

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ›

How we assess product sustainability ›

Environmental footprint

Total lifecycle Carbon footprint	**1**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Pro-active compliance (Product out of EU RoHS legal scope)**
REACh Regulation	**REACh Declaration**

Use Again

Repack and remanufacture

End of life manual availability	**End of Life Information**
Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony XB4

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws

Operating temperature from -40°C –to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Offer Marketing Illustration

Product benefits / Features

Image of product / Alternate images

Alternative

Life Is On | Schneider Electric