# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Acti9 remote indication iATLs

A9C15405

# Main

range of product	Acti9
Device short name	iATLs
Product or component type	Remote indication auxiliary
Signal contacts composition	1 C/O
Signalling circuit voltage	24 V AC/DC: 10 mA 12240 V AC: 50/60 Hz 6 A 1224 V DC: 6 A 15240 V AC: 50/60 Hz 2 A 1324 V DC: 2 A
[Uc] control circuit voltage	24240 V AC 50/60 Hz 24240 V DC

# Complementary

[Ui] rated insulation voltage	440 V	
[Uimp] rated impulse withstand voltage	4 kV	
Mounting mode	Fixed, on right side of TL	
Mounting support	DIN rail	
9 mm pitches	1	
Height	81 mm	
Width	9 mm	
Depth	69 mm	
Colour	White	
Connections - terminals	Tunnel type terminals0.54 mm² - rigid  Tunnel type terminals0.54 mm² - rigid - with cable end  Tunnel type terminals14 mm² - flexible  Tunnel type terminals14 mm² - flexible - with cable end	
Wire stripping length	11 mm	
Tightening torque	1 N.m	
Range compatibility	Acti9 iTL Acti9 iTLi Acti9 iTLs Acti9 iTLc Acti9 iTLm	
Product compatibility	ITL (32 A) ITL (16 A)	

# **Environment**

Overvoltage category III

IP degree of protection	IP20 conforming to IEC 60529	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-2050 °C	
Ambient air temperature for storage	-4070 °C	
Standards	EN/IEC 60669-2-2	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.1 cm
Package 1 Width	9.3 cm
Package 1 Length	7.7 cm
Package 1 Weight	40 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.6 cm
Package 2 Width	9.9 cm
Package 2 Length	26.5 cm
Package 2 Weight	531 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.267 kg

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

<b>⊘</b> Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	2
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

# Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No