Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



switch Acti9 iSW - 2 poles - 32 A - 415V

A9S60232

Main

Range	Acti9	
product name	Acti9 iSW	
Product or component type	Switch disconnector	
Device short name	iSW	
Device application	Control	
Poles description	2P	
Utilisation category	AC-22A	
Suitability for isolation	Yes	

Complementary

32 A at 415 V AC 50/60 Hz 415 V AC 50/60 Hz	
415 V AC 50/60 Hz	
415 V AC 50/60 Hz	
500 V AC 50/60 Hz conforming to EN/IEC 60669-2-4	
4 kV	
Toggle	
ON/OFF indication	
Yes	
Fixed	
DIN rail	
2	
77 mm	
18 mm	
70 mm	
White	
300000 cycles	
30000 cycles	
Tunnel type terminals - 10 mm² - rigid Tunnel type terminals - 10 mm² - flexible Tunnel type terminals - 10 mm² - flexible with ferrule	
9 mm	
1.2 N.m	

Environment

Standards	EN/IEC 60669-2-4	
IP degree of protection	IP4	
Pollution degree	2	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-2050 °C	
Ambient air temperature for storage	-4070 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.500 cm	
Package 1 Width	1.900 cm	
Package 1 Length	8.500 cm	
Package 1 Weight	66.000 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	12	
Package 2 Height	8.500 cm	
Package 2 Width	9.300 cm	
Package 2 Length	22.300 cm	
Package 2 Weight	840.000 g	
Unit Type of Package 3	S03	
Number of Units in Package 3	144	
Package 3 Height	30.000 cm	
Package 3 Width	30.000 cm	
Package 3 Length	40.000 cm	
Package 3 Weight	10.473 kg	

Contractual warranty



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances	
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No