

Product datasheet

Specifications



Downlight, Clipsal - Lighting, 750lm, recessed low glare, white

CLIPPDLLG

Main

Range	Clipsal
Product or component type	Downlight
Market segment	Residential
Main colour tint	White
Colour tint	White

Complementary

Device mounting	Ceiling
Rated power in W	7 W
Light source	LED
Total system power	230/240 V AC 50 Hz
Luminous flux	800 lm 3000 K 800 lm 4000 K 800 lm 6000 K
Colour rendering index	R _a =80
Bulb lifespan	35000 h
Beam angle	60 °
Trim width	103 mm
Trim height	86 mm
Cut-out dimensions	90 mm
Mounting depth	86 mm
Net weight	190 g

Environment

IP degree of protection	IP44
IK degree of protection	IK02
Insulation contact rating	IC-4
Unified glare rating	< 22

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	11 cm
Package 1 Length	11 cm
Package 1 Weight	283 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	23.3 cm
Package 2 Width	24.2 cm
Package 2 Length	57.9 cm
Package 2 Weight	6.141 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	640
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	210.512 kg

Contractual warranty

Warranty	3 Years
----------	---------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	332
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
Halogen content performance	Halogen free plastic parts product

Use Again

 Repack and remanufacture	
Circularity Profile	End of Life Information