

# Product datasheet

Specifications



## LED Diffused Batten, Clipsal - Lighting, 36W, 600mm, 4500lm, white

CLITPDB1200

### Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting
Market segment	Small commercial Residential

### Complementary

Type of installation	Indoor/outdoor
Total system power	36 W
Light source	LED 36 W
[Ue] rated operational voltage	230/240 V AC 50 Hz
Luminous flux	4500 lm
Bulb lifespan	50000 h
Colour temperature	3000 K 4000 K 5000 K
Device mounting	Surface
Mounting mode	Surface mounting
IP degree of protection	IP20
IK degree of protection	IK02
Electrical insulation class	Class I
Length	1200 mm
width	70 mm
Height	68 mm
Shape	Rectangular
Net weight	1550 g

### Environment

Colour rendering index	$R_a = 80$
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 % non-condensing

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	7.6 cm
Package 1 Length	123.3 cm
Package 1 Weight	1.862 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	18.5 cm
Package 2 Width	17.4 cm
Package 2 Length	131.5 cm
Package 2 Weight	8.14 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	120
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	135 cm
Package 3 Weight	267.2 kg

## Contractual warranty

Warranty	3 years
----------	---------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	<b>336</b>
---	------------

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	<b>No</b>
--	-----------

Packaging without single use plastic	<b>No</b>
--------------------------------------	-----------

<a href="#">EU RoHS Directive</a>	<b>Compliant</b>
-----------------------------------	------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Halogen content performance

**Halogen free plastic parts product**

Take-back

No

---

Image of product / Alternate images

Alternative

---







