PSA Panacom

PAN900SCHD

Video Intercom Surface Door Station



The PSA Panacom Surface Mount Door Station features an HD (2Mp) camera and connects to the Panacom PAN900MHS monitor or used as an additional camera for a Panacom Intercom kit.

The surface mount design allows for flexible installation in a variety of applications.

Features

HD Video

High definition 7" display with touch button controls and easy to use menu system for brightness, contrast, ring volume and ring tone control.

• Fasy Wiring

Easy to wire system using CAT5e/ CAT6 cable up to 50m between door and monitor.

Weather Resistant

IP65 Stainless steel flush mounted door camera with 2.0MP resolution and 120° Pinhole CMOS lens.

Customizable Hood

Includes a rain hood which can be easily attached or removed depending on installation requirements.

Specifications

_ '		
Camera		
Part Number	PAN900SCHD	
Camera Sensor	1.9mm 1/3" wide angle CMOS lens	
Viewing Angle	120° Horizontal	
Definition (Hor.)	2.0MP	
LED's for Night Vision	IR LED's (120°)	
Weatherproof IP Rating	IP65	
Material	Die Cast Metal	
Power Consumption	150mA max.	
Power	12VDC from Indoor Monitor	
Operating Temperature	-40° ~ +50° C	
Lock Output	12VDC, NO/NC Contact	
Installation Type	Surface Mounted	
Dimensions (H x W x D) (with rain hood)	130 x 40 x 40mm	


PSA Panacom

PAN900SCHD

Video Intercom Surface Door Station



System Wiring



Max. System: 2 doors stations to 4 internal monitors

Compatibility

PAN900MHD

Optional Accessories

- Additional Monitor (PAN900MHD)
- Flush Door Station (PAN900FCHD)
- Electric Door Strike (GEMGK310)
- Surface Door Station (PAN900SCHD)



Want an intercom connected to app, upgrade to the PSA Centrii video intercom system.

Scan the QR code for more information.

Item Code	PAN900SCHD	PAN900SCHD
Quantity	1	10
Barcode	XX	XX

