II CLIPSAL



Lamp LED, Airflow, suits 6500ADP-WE

6500LEDLAMP

Main

Range	Airflow
Product or component type	Downlight
Device application	Lighting
Market segment	Residential
Main colour tint	White
Colour tint	White

Complementary

Device mounting	Recessed ceiling
Rated power in W	8 W
Light source	LED
Total system power	230/240 V AC 50 Hz
Luminous flux	600 lm 3000 K warm white
Colour rendering index	R _a =80
load type	230 V AC LED lamp
Trim width	150 mm
Trim height	55 mm

Environment

Unified glare rating < 22

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	6.5 cm
Package 1 Length	6.5 cm
Package 1 Weight	96.7 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	15.5 cm
Package 2 Width	34.5 cm

Package 2 Length	68.5 cm
Package 2 Weight	5.835 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1200
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	155.04 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	48
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No