

MD6AFDDM40C

NHP MOD6+ Arc Fault Detection Device AFDD & MCB 6kA 1 Pole and Switched Neutral 40A C Curve



Component type	Miniature circuit breaker (MCB)
Range	MOD6+ Miniature Circuit Breakers
Model	N/A
Product status	New Item

NHP's MOD6+ range of miniature circuit breakers (MCB) offers cost effective solutions while providing core electrical protection, designed to detect and trip on overload and short circuit currents. These MCBs are available with a 6kA short circuit rating, with current ratings from 6-63A in 1P, 2P or 3P in C trip curve and 80-125A in 1P & 3P in C trip curve.

ELECTRICAL

Rated current	40 A
Number of poles (total)	2
Trip curve	C
Rated voltage	240 V
Frequency	50-60 Hz
Voltage type	AC
Service voltage Ub, AC	170 V
Rated short-circuit breaking capacity Icn according to AS/NZS 60898 at 230 VAC	6 kA
Rated short-circuit breaking capacity Icu according to AS/NZS 60947-2 at 230 VAC	6 kA
Max. rated operation voltage Ue	255 V
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4 kV
Concurrently switching neutral conductor	Yes

CONSTRUCTION

Number of protected poles	1
Degree of protection (IP)	IP40

MECHANICAL

Connectable conductor cross section solid-core	1-25 mm ²
Connectable conductor cross section multi-wired	1-25 mm ²

DIMENSIONS

Height	85 mm
Width	35.2 mm
Depth	75 mm
Width in number of modular spacings	2
Weight	0.18 kg

ENVIRONMENT

Pollution degree	2
------------------	---

MD6AFDDM40C

NHP MOD6+ Arc Fault Detection Device AFDD & MCB 6kA 1 Pole and Switched Neutral 40A C Curve



ENVIRONMENT

Rated surrounding temperature without derating	30 °C
Ambient temperature during operating	-25...55 °C