

PURO SLIM

PUROSL17W-300R
SAP CODE: 2002534



Minimalist design, maximum impact

The PURO SLIM is a sleek, IP54-rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature options, three size variations and available in black and white finishes, the PURO SLIM adapts seamlessly to diverse residential


APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180,113.1
 - C90/270,112.7

Photometric diagram shown is for 4000 K output.

KEY INFORMATION

Power	17 W
Lumen Output	1490 / 1625 / 1603 lm
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP54
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA10 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	88 / 96 / 94 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	Not Applicable
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	>85,000hrs @ Ta 45°C (L80)

ELECTRICAL

Input Voltage	
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Polypropylene
Diffuser Material	PMMA
Rebate Scheme Approvals	
Weight	0.6 kg
Dimensions	Ø 294 x 26 mm