

# **PROXIMA G2**

PROXIMA-12 SAP CODE: 2002529

### Sleek and robust

Experience the versatility and power of PROXIMA G2, a customisable and robust outdoor security lighting solution featuring flexible 360° pivot rotation and quick toolless installation.


Available as a single or twin lamp, PROXIMA G2 seamlessly blends into any

residential or commercial outdoor space, offering a sleek and stylish design.

#### **APPLICATIONS**


Shed, Carpark, Carport, Side of Building, Area Lighting

#### **DIMENSION DIAGRAMS**





## PHOTOMETRIC DIAGRAM



Unit: cd

- -C0/180 92.8deg
- -C30/210 92.9deg
- C60/240 92.8deg
- -C90/270 92.8deg

KEY INFORMATION	
Power	12W
Lumen Output	925 / 1087 / 1021 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Body Colour	Black (RAL9005)
IP Rating	IP54
IK Rating	IK10
Operating Ambient Temp.	0 to 40°C
Connection Type	PA12 Terminal Block
Driver	Integral
Warranty	3 yrs

Connection Type	PA12 Terminal Block
Driver	Integral
Warranty	3 yrs
PHOTOMETRIC	
Efficacy	77 / 96 / 86 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
Beam Angle	120°
Flicker-Free	No
Projected Lifespan	>50,000hrs@Ta25°C(L80)
Input Voltage	220-240V AC
Input Voltage Power Factor	220-240V AC > 0.5
Power Factor	> 0.5
Power Factor Electrical Classification	> 0.5 Class I
Power Factor Electrical Classification Surge Protection	> 0.5 Class I
Power Factor Electrical Classification Surge Protection OTHERS	> 0.5 Class I Overload / Short Circuit
Power Factor Electrical Classification Surge Protection OTHERS Body Material	> 0.5 Class I Overload / Short Circuit Aluminium and ABS

Ø114 x 202 mm

**Dimensions**