

Product datasheet

Specifications



LED Panel, Airflow, 15W, 47dB



CPL7000FLH-WE

Main

Range of product	Airflow
Range	Airflow
Product brand	Clipsal
Product or component type	Fan, Light and Heater units
Product destination	Ceiling fitting
Device application	Duct
Main colour tint	White
Colour tint	White

Complementary

[Ue] rated operational voltage	230/240 V AC 50 Hz
Air flow	400 m3/h
Power consumption in W	1085 W
Cut-out dimensions	616 x 325 mm
Depth	190 mm
Air discharge option	Downflow
Noise level	47 dB
Fan type	Centrifugal
Light source	LED 15 W
Heat dissipation	1000 W

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39 cm
Package 1 Width	40.5 cm
Package 1 Length	71.5 cm
Package 1 Weight	12.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	110 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	114 cm
Package 2 Length	114 cm
Package 2 Weight	115 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	1533
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again

 Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative







