# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# **II CLIPSAL**

# LED Downlight, Airflow, 7W, 45dB



CPL7600ATP-WE

## Main

Range of product	Airflow	
Range	Airflow	
Product brand	Clipsal	
Product or component type	Fan, Light and Heater units	
Product destination	Ceiling fitting	
Device application	Duct	
Main colour tint	White	
Colour tint	White	

# Complementary

[Ue] rated operational voltage	230/240 V AC 50 Hz	
air flow	300 m3/h	
Power consumption in W	590 W	
Cut-out dimensions	470 x 270 mm	
Depth	200 mm	
Air discharge option	Downflow	
Noise level	45 dB	
Fan type	Centrifugal	
Light source	LED 7 W	
Heat dissipation	275 W	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43 cm
Package 1 Width	33 cm
Package 1 Length	53.7 cm
Package 1 Weight	6.3 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Height	110 cm

Package 2 Width	114 cm
Package 2 Length	114 cm
Package 2 Weight	90.6 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3287
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
China RoHS Regulation	China RoHS declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No