

CrossLine Light Strip

The Crossline is the latest generation LED cove lighting from Pierlite. This comprehensive new family of flexible strip lights are designed to follow straight lines and corners to create beautiful ambiances that highlight architectural details. These lighting strips also promise excellent energy-saving performance, superb lighting uniformity, and colour consistency. All with a long lifetime that promises less lumen decay or colour shifts.



COLOUR SELECT

- Available in Dot and Dotless version in single colour or Colour Select (3000K/4000K/6500K) in high CRI90 colour quality.
- Self-adhesive 3M tape on the back for simple and reliable mounting on various surfaces.
- One box solution with 24V SELV power supply and a set accessories included to enable easy and fast assembly



90

CRI



IP20

Ingress
Protection
Rating



4SDCM

MacAdam
Steps



0 to 40

Operating
Temperature



50,000hrs
(L70/B50)

Lifetime



5 Years

Warranty

CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	LINE CURRENT
CLC05L06930I2E	35W	660lm	100lm/W	3000K	L500 x W10 x H1.25 mm	0.37kg	0.50A	0.16A
CLC05L06940I2E	35W	660lm	100lm/W	4000K	L500 x W10 x H1.25 mm	0.37kg	0.50A	0.16A
CLC05L069CSI2E	35W	660lm	100lm/W	4000K	L500 x W10 x H1.25 mm	0.37kg	0.50A	0.16A
CLL02L069CSI2E	12W	650lm	100lm/W	4000K	L200 x W10 x H1.25 mm	0.28kg	0.20A	0.08A
CLL05L06930I2E	30W	350lm	100lm/W	3000K	L500 x W10 x H1.25 mm	0.36kg	0.50A	0.16A
CLL05L06940I2E	30W	650lm	100lm/W	4000K	L500 x W10 x H1.25 mm	0.36kg	0.90A	0.15A
CLL05L069CSI2E	30W	650lm	100lm/W	4000K	L500 x W10 x H1.25 mm	0.36kg	0.50A	0.16A



CLC05L069CSi2E, CLC05L06930i2E, CLC05L06940i2E



CLL05L06930i2E, CLL05L06940i2E, CLL02L069CSi2E,
CLL05L069CSi2E

