

Product datasheet

Specifications

CLIPSAL



Meter box, Resi MAX, 24 modules with meter isolator MCB

230DRAT2

Main

Range of product	Resi MAX
Product type	Meter box
Enclosure type	Plain door enclosure
Device application	Distribution Metering
Targeted country	Australia

Complementary

Enclosure mounting	Surface Flush
Number of modules	24
Provided equipment	Enclosure DIN rail Earth and neutral grid assembly Removable meter panel Fascia plate
Function available	Clips lead retainer
Cable entry	knock-out top and bottom
Type of door	Ventilated removable door with door retainer
Door opening side	Right
Lock type	Padlockable
Material	Iron (galvanised)
Surface finish	Epoxy powder coat
Width	485 mm
Height	680 mm
Depth	256 mm
Colour	Beige

Environment

IP degree of protection	IP23
Standards	AS/NZS 3000

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	70 cm
Package 1 Width	27.4 cm
Package 1 Length	51.5 cm
Package 1 Weight	19.5 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 169

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

Halogen-free status Halogen free product

PVC free No

Silicone-free No

Use Again

Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

Image of product / Alternate images

Alternative

