# **II CLIPSAL**



# Miniature Circuit Breaker, Max9, 1P+N, 25A, C curve, 6000A

MX9MN125

# Main

Range	MAX9	
Product or component type	Miniature circuit-breaker	
Device application	Distribution	
Poles description	1P + N	
Number of protected poles	1	
[In] rated current	25 A at 30 °C	
Network type	AC	
Network frequency	50/60 Hz	
[Ue] rated operational voltage	240 V AC 50/60 Hz	
Curve code	С	
Magnetic tripping limit	510 x ln	
Colour	White (RAL 9003)	

# Complementary

Breaking capacity	6000 A Icn at 240 V AC 50/60 Hz conforming to AS/NZS 60898	
[Ics] rated service breaking capacity	6000 A 100 % - 240 V AC 50/60 Hz	
Limitation class	3	
[Uimp] rated impulse withstand voltage	4 kV	
[Ui] rated insulation voltage	400 V	
Contact position indicator	Yes	
Control type	Toggle	
Local signalling	ON/OFF indication	
Height	85 mm	
Width	18 mm	
Depth	71 mm	
Mechanical durability	20000 cycles	
Electrical durability	20000 cycles	
Connections - terminals	Tunnel type terminals (top or bottom) 110 mm² flexible Tunnel type terminals (top or bottom) 116 mm² rigid	
Wire stripping length	14 mm for top or bottom connection	
Tightening torque	2 N.m	

Grid distance 45 mm

# **Environment**

RCM
IP20
2
95 % at 55 °C
02000 m
-2570 °C
-4085 °C
-25 °C (30.08 A) -20 °C (29.66 A) -15 °C (29.23 A) -10 °C (28.79 A) -5 °C (28.34 A) 0 °C (27.89 A) 5 °C (27.43 A) 10 °C (26.96 A) 15 °C (26.48 A) 20 °C (26.0 A) 25 °C (25.5 A) 30 °C (25.0 A) 35 °C (24.49 A) 40 °C (23.96 A) 45 °C (23.42 A) 50 °C (22.87 A) 55 °C (22.87 A) 55 °C (22.13 A) 66 °C (21.28 A)

# **Packing Units**

racking onlis	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.4 cm
Package 1 Width	1.8 cm
Package 1 Length	9.4 cm
Package 1 Weight	115 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	22 cm
Package 2 Width	9.9 cm
Package 2 Length	8.7 cm
Package 2 Weight	1.49 kg
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	13.95 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	5
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	No

## **Use Again**

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No

### Offer Marketing Illustration

#### Product benefits / Features

# **Technical Benefits**

# MAX9



MAX Speed - up to 15 times faster with MAXBAR



MAX Flexibility -compatible with MAX9 PRO DBs & MAXBAR









**Technical Illustration** 

# Assembly's dimensions

