

# MOUNTABLE POWERBOARD WMS-02-STD 52A

Designed and tested in accordance  
with AS/NZS61439.4



✓ **MINING**  
AS/NZS3012

✓ **CONSTRUCTION**  
AS/NZS3012

✓ **EVENTS**  
AS/NZS3002



Registered Design No. 202014205

RDF - 0.5  
max 26A under full load

What is RDF?  
[Click Here](#)



## SPECIFICATIONS

Supply Inlet	Internal terminals ready for connection
Alternative Supply	Connected cable
Outlets	1 x 32A 415V 5 pin switched IP66 2 x 15A 240V 3 pin auto switched IP66
Materials	UV resistant high impact corrosion resistant V5 polyethylene
Dimensions	15 kg - 57cm (H) x 40cm (W) x 29cm (D)

## KEY FEATURES

**Main Isolating Switch** not behind a window  
**Lockable** hinged door & windows with pad lock  
**Breather Valve** reduced condensation in board  
**Three Phase Outlet** with a rotary switch  
**Mounting Brackets** supplied for easy installation  
**Entire Board is IP65** not just the outlets  
**Ready-Made** for generators, wall mounts or portable frames.



**YOUR PARTNER IN  
PORTABLE POWER DISTRIBUTION**

1800 338 979 | [sales@powersafe.net.au](mailto:sales@powersafe.net.au)  
[www.powersafe.net.au](http://www.powersafe.net.au)