

LED wall light, Clipsal, 9W, 4000K, IP54, silver

CLITPWL

Main

Range	Clipsal
Product name	TPWL Series
Product or component type	Wall light
Device application	Lighting

Complementary

Type of installation	Outdoor	
Total system power	9 W	
Light source	LED	
[Ue] rated operational voltage	230240 V AC 50 Hz	
Colour rendering index	R _a =80	
Luminous flux	260 lm 350 lm 410 lm	
Bulb lifespan	15000 h	
Colour temperature	3000 K 4000 K 6500 K	
Provided equipment	Allen key 2 screws Washer	
Device mounting	Wall mounted	
Mounting mode	Surface mounted	
fixing mode	Screwed	
Electrical insulation class	Class I	
Shape	Cylindrical	
Height	210 mm	
Length	60 mm	
Width	80 mm	
Depth	100 mm	
Net weight	710 g	
Targeted country	Australia	

Environment

IP degree of protection	IP54
IK degree of protection	IK10
Ambient air temperature for operation	-1045 °C
Relative humidity	1095 % non-condensina

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20 cm
Package 1 Width	6.4 cm
Package 1 Length	19.8 cm
Package 1 Weight	505 g
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	22 cm
Package 2 Width	27.7 cm
Package 2 Length	41.5 cm
Package 2 Weight	4.52 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	320
Package 3 Height	104.8 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	195 kg

Contractual warranty

Warranty (in months)

18



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	117
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

Alternative





CLITPWL





CLITPWL





CLITPWL

