# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# **II CLIPSAL**



# LED wall light, Clipsal, 9W, 4000K, IP54, black

CLITPWLBK

### Main

Range	Clipsal
Product name	TPWL Series
Product or component type	Wall light
Device application	Lighting

### Complementary

Complementary		
Type of installation	Outdoor	
Total system power	9 W	
Light source	LED	
[Ue] rated operational voltage	230240 V AC 50 Hz	
Colour rendering index	R <sub>a</sub> =80	
Luminous flux	260 lm	
	350 lm	
	410 lm	
Bulb lifespan	15000 h	
Colour temperature	3000 K	
	4000 K	
	6500 K	
Colour	Black	
Provided equipment	Allen key	
	2 screws	
	Washer	
Device mounting	Wall mounted	
Mounting mode	Surface mounted	
fixing mode	Screwed	
Electrical insulation class	Class I	
Shape	Cylindrical	
Height	210 mm	
Length	60 mm	
Width	80 mm	
Depth	100 mm	
Net weight	716 g	
Targeted country	Australia	

# **Environment**

IP degree of protection	IP54	
IK degree of protection	IK10	
Ambient air temperature for operation	-1045 °C	
Relative humidity	1095 % non-condensing	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.2 cm
Package 1 Width	8.4 cm
Package 1 Length	10.7 cm
Package 1 Weight	816 g
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	25.2 cm
Package 2 Width	23.3 cm
Package 2 Length	27.3 cm
Package 2 Weight	5.14 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	288
Package 3 Height	91.2 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	246 kg

# **Contractual warranty**

Warranty (in months)

18



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Total lifecycle Carbon footprint	117
Environmental Disclosure	Product Environmental Profile

### **Use Better**

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No

Image of product / Alternate images

### **Alternative**





# CLITPWLBK





# **CLITPWLBK**



# **CLITPWLBK**

