Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

II CLIPSAL



Switch, Clipsal Solis T Series, 2 gangs, horizontal, 16AX/20A, brushed brass

1042TA-BB

Main

Range	Clipsal Solis T Series	
Product brand	Clipsal	
Product or component type	Switch	
Assembly Type	Complete product	
Outlet standard deviation	Australian/New Zealand	
Colour tint	Brushed brass	

Complementary

2 gangs	
230/240 V	
AC	
50 Hz	
20 A/16 AX	
Toggle switch	
Screw terminals	
Flush	
2	
Aluminium	
Horizontal	
Metallic	
LEDi lamp 0250 W 20 A/16 AX	
4 x 1.53 x 2.5 mm²	
Philips No 2 Square drive no 1 (SQ1)	
10 mm	
Screw	
3.6 mm	
84 mm	
93 x 50 mm	
RCM	
Anodised	
74 mm	

Width	148 mm
Depth	56 mm
Embedding depth	41 mm
Motor M-rating AS3133	M80
Switch function	1-pole 1/2-way

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZS 60669

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	8 cm
Package 1 Length	8 cm
Package 1 Weight	100 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	34 cm
Package 2 Width	36 cm
Package 2 Length	48 cm
Package 2 Weight	3.084 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	2
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No

1042TA-BB

Image of product / Alternate images

Alternative













