

# PRODUCT DATASHEET

## ECO WIDE WP LWPE4F40MW 40/35/30/20W TRI

ECO IP65 WIDE BODY BATTEN | Delivering versatile, flicker-free illumination, the 115mm wide-body batten offers multi-watt and tri-colour selection, engineered for quick installation and seamless retrofit.



---

### Areas of application

- Car parks
- Public areas
- Warehouses
- Railways
- Commercial Areas

---

### Product benefits

- Versatility & Energy Savings
- Customized Ambiance & Flexibility
- Easy Retrofit & Aesthetics
- Durability & Protection
- Fast, Easy Wiring & Secure Connection

---

### Product features

- Multi-watt selectable: 40W/35W/30W/20W
- Tri color selectable: 3000K/4000K/5700K
- 115 mm wide body fits retrofits perfectly and hides old ceiling marks
- Two-piece construction with encapsulated module for quick and hassle-free installation
- Flicker free
- Available with emergency option
- Removable 6 mm PA16 terminal block allows fast, easy wiring and secure connections

## TECHNICAL DATA

### Electrical data


|   |                           |
|---|---------------------------|
| Nominal wattage   | 40 W / 35 W / 30 W / 20 W |
| Nominal voltage   | 220...240 V               |
| Mains frequency   | 50...60 Hz                |
| Nominal current   | 240.000 mA                |
| Inrush current  | 12.9 A                    |
| Inrush current time $T_{h50}$                               | 195 $\mu$ s               |
| Max. number of luminaires per miniature circuit breaker B16 | 26                        |
| Max. number of luminaires per miniature circuit breaker C10 | 27                        |
| Max. number of luminaires per miniature circuit breaker C16 | 44                        |
| Power factor $\lambda$                                      | > 0.90                    |
| Total harmonic distortion                                   | < 20 %                    |
| Protection class  | I                         |

### Photometrical data

|                                      |   |
|--------------------------------------|---|
| Luminous flux                        | 4000 lm / 3500 lm / 3000 lm / 2000 lm   |
| Luminous efficacy                    | 100 lm/W                                |
| Color temperature                    | 3000 K / 4000 K / 5700 K                |
| Light color (designation)            | Warm White / Cool Daylight / Cool White |
| Color rendering index Ra             | 80                                      |
| Standard deviation of color matching | < 6 sdc <sub>m</sub>                    |
| Low flicker                          | Yes                                     |
| Flickering metric (Pst LM)           | $\leq$ 1                                |
| Beam angle                           | 120 °                                   |

### Dimensions & Weight

|                |            |
|----------------|------------|
| Length         | 1255.00 mm |
| Width          | 115.00 mm  |
| Height         | 85.00 mm   |
| Product weight | 2200.00 g  |



## ECO WEATHERPROOF BATTEN

### Materials & Colors

|  |                    |
|--|--------------------|
| Product color                              | Grey               |
| Housing color                              | Grey               |
| Body material                              | Plastic            |
| Cover material                             | Polycarbonate (PC) |
| Light emitting surface material            | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C             |

### Application & Mounting

|  |                            |
|--|----------------------------|
| Ambient temperature range              | -20...+40 °C               |
| Temperature range at storage           | 0...+40 °C                 |
| Type of connection                     | Screwless terminal, 4-Pole |
| Type of protection                     | IP65/IP65                  |
| Protection class IK (shock resistance) | IK08                       |
| Dimmable                               | No                         |
| Mounting type                          | Surface/Suspended          |
| Mounting location                      | Ceiling / Wall             |
| Replaceable light source               | No                         |

### Lifespan

|                           |                       |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 70000 h <sup>1)</sup> |
| Lifespan L80/B10 at 25 °C | 50000 h <sup>1)</sup> |
| Lifespan L80/B50 at 25 °C | 50000 h               |
| Lifespan L90/B10 at 25 °C | 35000 h               |

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Control gear

|                |                    |
|----------------|--------------------|
| Output current | 200/250/300/350 mA |
|----------------|--------------------|

## Certificates & Standards

|                                  |                 |
|----------------------------------|-----------------|
| Standards                        | CE / RCM        |
| Replaceable light source (EPREL) | Not replaceable |

## DOWNLOAD DATA

| Documents and certificates  | Document name           |
|---|-------------------------|
|  User instruction / safety instructions | ECO WEATHERPROOF BATTEN |

| Photometric and lighting design files   | Document name           |
|---|-------------------------|
|  IES file (IES) | ECO WEATHERPROOF BATTEN |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854612077 | Folding box<br>1             | 1,260 mm x 120 mm x 90 mm            | 2260.00 g    | 13.61 dm <sup>3</sup> |
| 4099854537264 | Shipping box<br>6            | 1,275 mm x 255 mm x 290 mm           | 13960.00 g   | 94.29 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.