



**This item includes:**

 <p><b>Item No.: 221-412</b></p> <p>Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 2-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-413</b></p> <p>Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 3-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-415</b></p> <p>Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-500</b> <b>10</b></p> <p>Mounting carrier; 221 Series - 4 mm<sup>2</sup>; for DIN-35 rail mounting/screw mounting; orange</p>
 <p><b>Item No.: 221-615</b> <b>30</b></p> <p>Splicing connector with levers; for all conductor types; max. 6 mm<sup>2</sup>; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm<sup>2</sup>; transparent</p>			

**Notes**

General safety information

**NOTICE: Observe installation and safety instructions!**

- **Only to be used by electricians!**
- Do not work under voltage/load!
- Use only for proper use!
- Observe national regulations/standards/guidelines!
- Observe technical specifications for the products!
- Observe the number of permissible potentials!
- Do not use damaged/dirty components!
- Observe conductor types, cross-sections and strip lengths!
- Insert conductor until it hits the product's backstop!
- Use original accessories!

**To be sold only with installation instructions!**

**Physical data**

Width	445 mm / 17.519 inches
Height	118 mm / 4.646 inches
Depth	358 mm / 14.094 inches

**Material data**

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	27 MJ
Weight	3552.9 g

**Commercial data**

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	QU
GTIN	4066966130584
Customs tariff number	80808080888

**Product Classification**

UNSPSC	39121409
ETIM 9.0	EC000446
ETIM 10.0	EC000524
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads****Environmental Product Compliance****Compliance Search**Environmental Product  
Compliance 887-928